NEW SOURCE CONSTRUCTION PERMIT and MINOR SOURCE OPERATING PERMIT OFFICE OF AIR QUALITY and Anderson Office of Air Management

iPower Technologies, LLC 1819 West 38th Street Anderson, Indiana 46013

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-5.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Operation Permit No.: MSOP 095-1478100106	
Issued by: Original signed by Paul Dubenetzky Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: November 5, 2001

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]
- A.2 Emission Units and Pollution Control Equipment Summary
- A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONSTRUCTION CONDITIONS

- B.1 Permit No Defense [IC 13]
- B.2 Definitions
- B.3 Effective Date of the Permit [IC 13-15-5-3]
- B.4 Revocation of Permits [326 IAC 2-1.1-9(5)]
- B.5 Modification to Permit [326 IAC 2]
- B.6 Minor Source Operating Permit [326 IAC 2-6.1]

C SOURCE OPERATION CONDITIONS

- C.1 PSD Minor Source Status [326 IAC 2-2]
- C.2 Preventive Maintenance Plan [326 IAC 1-6-3]
- C.3 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]
- C.4 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]
- C.5 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]
- C.6 Permit Revocation [326 IAC 2-1-9]
- C.7 Opacity [326 IAC 5-1]
- C.8 Fugitive Dust Emissions [326 IAC 6-4]
- C.9 Performance Testing [326 IAC 3-6]
- C.10 Monitoring Methods [326 IAC 3]

Record Keeping and Reporting Requirements

- C.11 Malfunctions Report [326 IAC 1-6-2]
- C.12 Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-3]
- C.13 General Record Keeping Requirements [326 IAC 2-6.1-2]
- C.14 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]
- C.15 Annual Notification [326 IAC 2-6.1-5(a)(5)]

D.1 EMISSIONS UNIT OPERATION CONDITIONS -Ten (10) natural gas-fired space heaters,

Three (3) natural gas-fired engine test stands, one (1) epoxy dip tank, which is capable of coating stator coils at a maximum rate of 300 per hour; and one (1) electric drying oven, at a rated capacity of 108 kw.

Emission Limitations and Standards

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

Compliance Determination Requirements

D.1.2 Testing Requirements

- D.1.3 Volatile Organic Compounds (VOC)D.1.4 VOC Emissions

Record Keeping and Reporting RequirementsD.1.5 Record Keeping Requirements

- D.1.6 Reporting Requirements

Annual Notification Malfunction Report

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) and Anderson Office of Air Management. The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates stationary source that manufactures stator engine components.

Authorized Individual: iPower Technologies, LLC

Source Address: 1819 West 38th Street, Anderson, Indiana 46013 Mailing Address: 2902 Enterprise Drive, Anderson, Indiana 46013

Phone Number: (765) 779-5539

SIC Code: 8734 County Location: Madison

County Status: Attainment for all criteria pollutants
Source Status: Minor Source Operating Permit
Minor Source, under PSD

A.2 Emissions units and Pollution Control Equipment Summary

This stationary source is approved to construct and operate the following emissions units and pollution control devices:

- (a) Ten (10) natural gas-fired space heaters, identified as 1-10 with a total heat input capacity of 1.75 million British Thermal Units per hour (mmBtu/hr);
- (b) Three (3) natural gas-fired engine test stands, each with an output rated of 150 kilowatt (kw);
- (c) One (1) epoxy dip tank, identified as PDG-U500, which is capable of coating stator coils at a maximum rate of 300 per hour; and
- (d) One (1) electric drying oven, at a rated capacity of 108 kw.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is not required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is not a major source, as defined in 326 IAC 2-7-1(22); and
- (b) This is the first air approval issued to the source.

SECTION B GENERAL CONSTRUCTION CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Permit No Defense [IC 13]

This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this permit if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Modification to Permit [326 IAC 2]

Notwithstanding the Section B condition entitled "Minor Source Operating Permit", all requirements and conditions of this construction permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

B.6 Minor Source Operating Permit [326 IAC 2-6.1]

This document shall also become a minor source operating permit pursuant to 326 IAC 2-6.1 when, prior to start of operation, the following requirements are met:

- (a) The attached Affidavit of Construction shall be submitted to the Office of Air Quality (OAQ), Permit Administration & Development Section.
 - (1) If the Affidavit of Construction verifies that the facilities covered in this Construction Permit were constructed as proposed in the application, then the facilities may begin operating on the date the Affidavit of Construction is postmarked or hand delivered to IDEM.
 - (2) If the Affidavit of Construction does not verify that the facilities covered in this Construction Permit were constructed as proposed in the application, then the Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section prior to beginning operation of the facilities.
- (b) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (c) Upon receipt of the Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section, the Permittee shall attach it to this document.

- (d) The operation permit will be subject to annual operating permit fees pursuant to 326 IAC 2-1.1-7(Fees).
- (e) Pursuant to 326 IAC 2-6.1-7, the Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date established in the validation letter. If IDEM, OAQ, and Anderson Office of Air Management, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied. The operation permit issued shall contain as a minimum the conditions in Section C and Section D of this permit.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

C.1 PSD Minor Source Status [326 IAC 2-2] [40 CFR 52.21]

The total source potential to emit of nitrogen oxides (NOx) is less than 250 tons per year. Therefore the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) and 40 CFR 52.21 will not apply.

C.2 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) after issuance of this permit, including the following information on each emissions unit:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that failure to implement the Preventive Maintenance Plan does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAQ, and Anderson Office of Air Management upon request and shall be subject to review and approval by IDEM, OAQ and Anderson Office of Air Management. IDEM, OAQ, and Anderson Office of Air Management may require the Permittee to revise its Preventive Maintenance Plan whenever lack of proper maintenance causes or contributes to any violation.

C.3 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management P.O. Box 2100 120 East 8th Street Anderson, Indiana 46011

Any such application should be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1.

(c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

C.4 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, Anderson Office of Air Management, and U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;
- (c) Inspect, at reasonable times, any processes, emissions units (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit or any operating permit revisions;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

C.5 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to [326 IAC 2-6.1-6(d)(3)]:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch and Anderson Office of Air Management within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAQ, and Anderson Office of Air Management shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

C.6 Permit Revocation [326 IAC 2-1-9]

Pursuant to 326 IAC 2-1-9(a)(Revocation of Permits), this permit to construct and operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.

- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM and Anderson Office of Air Management, the fact that continuance of this permit is not consistent with purposes of this article.

C.7 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.8 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

Testing Requirements

C.9 Performance Testing [326 IAC 3-6]

(a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management P.O. Box 2100 120 East 8th Street Anderson, Indiana 46011

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

(b) All test reports must be received by IDEM, OAQ and Anderson Office of Air Management within forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, and Anderson Office of Air Management if the source submits to IDEM, OAQ, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

Compliance Monitoring Requirements

C.10 Monitoring Methods [326 IAC 3]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

Record Keeping and Reporting Requirements

C.11 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.12 Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-13]

(a) With the exception of performance tests conducted in accordance with Section C-Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.

- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM and Anderson Office of Air Management may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.13 General Record Keeping Requirements [326 IAC 2-6.1-2]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAQ, and Anderson Office of Air Management representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner or Anderson Office of Air Management makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner or Anderson Office of Air Management within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses:
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;

- (4) Records of preventive maintenance shall be sufficient to demonstrate that failure to implement the Preventive Maintenance Plan did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C Compliance Monitoring Plan Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented when operation begins.

C.14 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Semi-annual Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported. The Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management P.O. Box 2100 120 East 8th Street Anderson, Indiana 46011

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and Anderson Office of Air Management on or before the date it is due.
- (d) Unless otherwise specified in this permit, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
- (2) A malfunction as described in 326 IAC 1-6-2; or
- (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
- (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.

- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

C.15 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) Annual notification shall be submitted to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) Noncompliance with any condition must be specifically identified. If there are any permit conditions or requirements for which the source is not in compliance at any time during the year, the Permittee must provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be, achieved. The notification must be signed by an authorized individual.
- (c) The annual notice shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in the format attached no later than March 1 of each year to:

Compliance Data Section, Office of Air Quality Indiana Department of Environmental Management 100 North Senate Avenue, P.O. Box 6015 Indianapolis, IN 46206-6015

and

Anderson Office of Air Management P.O. Box 2100 120 East 8th Street Anderson, Indiana 46011

(d) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and Anderson Office of Air Management on or before the date it is due.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

- (a) Ten (10) natural gas-fired space heaters, identified as 1-10 with a total heat input capacity of 1.75 million British Thermal Units per hour (mmBtu/hr);
- (b) Three (3) natural gas-fired engine test stands, each with an output rated of 150 kilowatt (kw);
- (c) One (1) epoxy dip tank, identified as PDG-U500, which is capable of coating stator coils at a maximum rate of 300 per hour; and
- (d) One (1) electric drying oven, at a rated capacity of 108 kw.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

The Epoxy Dip Tank, PDG-U500 emits an actual VOC emissions of less than 15 pounds per day. Any changes which may increase the Epoxy Dip Tank, PDG-U500 actual VOC emissions to 15 pounds per day shall obtain OAQ approval before such change may occur and be subject to 326 IAC 8-2-9 (Miscellaneous Metal Coating).

Compliance Determination Requirements

D.1.2 Testing Requirements [326 IAC 2-1.1-11]

The Permittee is not required to test this emissions unit by this permit. However, IDEM may require compliance testing when necessary to determine if the emissions unit is in compliance. If testing is required by IDEM or Anderson Office of Air Management, compliance with the VOC limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.3 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAQ, and Anderson Office of Air Management reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.4 VOC Emissions

Compliance with Condition D.1.1 shall be demonstrated within 30 days of the end of each month based on the total volatile organic compound usage for the most recent twelve (12) month period.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.5 Record Keeping Requirements

(a) To document compliance with Conditions D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken (monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1

- (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
- (2) A log of the dates of use;
- (3) The VOC content of the coatings used for each month;
- (4) The cleanup solvent usage for each month;
- (5) The total VOC usage for each month; and
- (6) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

D.1.6 Reporting Requirements

The Permittee is not required to submit reports on these facilities by this permit. However, IDEM may require reporting when necessary to determine if the facility in compliance. If reporting is required by IDEM, reports shall be submitted in accordance with Section C - Reporting Requirements.

iPower Technologies, LLC
Anderson, Indiana
Permit Reviewer: Aida De Guzman

Page 17 of 19
MSOP 095-14781-00106

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

MINOR SOURCE OPERATING PERMIT ANNUAL NOTIFICATION

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

iPower Technologies, LLC

Company Name:

Address:	1819 West 38 th Street
City:	Anderson
Phone #:	(765)779-5539
MSOP #:	095-14781-00106
hereby certify that	iPower Technologies, LLC is 9 still in operation.
	9 no longer in operation.
hereby certify that	iPower Technologies, LLC is 9 in compliance with the requirements of MSOP 095-14781-00106.
	9 not in compliance with the requirements of MSOP 095-14781-00106.
Authorized Indivi	dual (typed):
Title:	
Signature:	
Date:	
If there are any con	
description of how t	ditions or requirements for which the source is not in compliance, provide a narrative he source did or will achieve compliance and the date compliance was, or will be

MALFUNCTION REPORT

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY FAX NUMBER - 317 233-5967

This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4. THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR COMBINATION HAZARDOUS AIR POLLUTANT? _____, 1 TONYEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD? _____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2)? _____ EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC ______ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE? Y THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT? Y Ν iPower Technologies, LLC PHONE NO. (765) 779-5539 LOCATION: (CITY AND COUNTY) Anderson, Madison AFS PLANT ID: _095-00106 AFS POINT ID: PERMIT NO. 095-14781 INSP. CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON:___ DATE/TIME MALFUNCTION STARTED: ____/ 19____ _____/ 19______ ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE_____/ 19_____ AM/PM TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: MEASURES TAKEN TO MINIMIZE EMISSIONS:____ REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS: CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: INTERIM CONTROL MEASURES: (IF APPLICABLE) MALFUNCTION REPORTED BY: ____TITLE:____ (SIGNATURE IF FAXED) DATE: TIME: MALFUNCTION RECORDED BY:____

*SEE PAGE 2

Please note - This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

*<u>Essential services</u> are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Indiana Department of Environmental Management Office of Air Quality and Anderson Office of Air Management

Technical Support Document (TSD) for a New Source Construction and Minor Source Operating Permit

Source Background and Description

Source Name: iPower Technologies, LLC

Source Location: 1819 West 38th Street, Anderson, Indiana 46013

County: Madison SIC Code: 8734

Operation Permit No.: 095-14781-00106 Permit Reviewer: Aida De Guzman

The Office of Air Quality (OAQ) has reviewed an application from iPower Technologies, LLC relating to the construction and operation of the following new equipment to be used in the manufacture of stator engine components:

- (a) Ten (10) natural gas-fired space heaters, identified as 1-10 with a total heat input capacity of 1.75 million British Thermal Units per hour (mmBtu/hr);
- (b) Three (3) natural gas-fired engine test stands, each with an output rated of 150 kilowatt (kw);
- (c) One (1) epoxy dip tank, identified as PDG-U500, which is capable of coating stator coils at a maximum rate of 300 per hour; and
- (d) One (1) electric drying oven, at a rated capacity of 108 kw.

Currently, there are no emission units at the source.

Source Definition

The following five (5) plants were determined to be separate from one another in a previous Registration 095-12445-00105 issued on August 21, 2000 to Delco Remy America, Inc. located at 7825 American Way, Anderson, Indiana:

- (a) Delco Remy America , Inc. Plant 4, is currently empty because all its existing emission units were removed. This plant is now called iPower Technologies, LLC which is being permitted under this permit (095-14781-00106) is located at Independence Park, 1819 West 38th Street. This plant tests and manufactures stator motors, with SIC code 8734. It is located approximately 1½ mile from plant 5, 6 miles from plants 1 and 2, and 7½ miles from plant 3.
- (b) Plant 1 is located at 6512 Production Road. This plant is used for engine testing for prototypes stator motors, with a Standard Industrial Classification (SIC) code 8734. It is located approximately 8 miles from plant 3 (7825 American Way), 1/4 mile from plant 2, 5 miles from plant 5 and 6 miles from plant 4.

Permit Reviewer: Aida De Guzman

- (c) Plant 2 is located at 6628 Production Road. This plant assembles heavy duty-alternators, with an SIC code 3714.
- (d) Plant 3 in this application is located at 7825 American Way. This plant assembles light and heavy duty stator motors, with an SIC code of 3714. It is located approximately 7½ miles from plants 4 and 5, and 8 miles from plants 1 and 2.
- (e) Plant 5 is located at 4640 Pendleton Avenue. This plant assembles engine alternator and other engine components, with SIC code 3714. It is located approximately 1½ mile from plant 4.

These five (5) plants are all owned by one (1) company. Three (3) plants have the same SIC Code of 3714, and two (2) plants have the same SIC Code of 8734. There are no parts or product being transferred from one plant to another plant for further processing, and therefore, there is no support relationship between the plants.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
Engine Test Stands	Engine Test Stands	17	0.33	100	100
Epoxy Dip Tank/Oven	Epoxy Dip Tank/Oven	34	2	3,500	400

Recommendation

The staff recommends to the Commissioner that the construction and operation be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

A complete application for the purposes of this review was received on August 13, 2001.

Emission Calculations

- (a) Natural Gas Combustion Emissions from Space Heaters: See Page 1 of 2 TSD Appendix A for detailed calculations.
- (b) Dip Coating Emissions: See Page 2 of 2 TSD Appendix A for detailed calculations.
- (c) Engine Test Stands Emissions:

Output Rate/Engine - 150 KW

Total Heat Input Rate - 150 KW * 3 units * 3,414.4 Btu/hr

KW

* mm/1,000,000

= 1.536 mmBtu/hr

1 CF = 1,050 Btu natural gas (Heating Value)

1,530,000 Btu/hr * cuft/1050 Btu = 12,764,571 CF/yr

* 8760 hrs/yr

Pollutants	Emission Factor (lb/mmBtu) SCC 2-02-002-54)	Emission (tons/year)		
PM	9.9 x 10 ⁻³	0.066		
PM10	7.7 x 10 ⁻⁵	0.0005		
СО	8.47 x 10 ⁻¹	5.7		
VOC	1.18 x 10 ⁻¹	0.79		
SO2	5.88 x 10 ⁻⁴	0.004		
NOx	4.08 lb/mmBtu	27.46		

Methodology:

Emissions = Heat input, mmBtu/hr *Ef. lb/mmBtu * ton/2000 lb * 8760 hrs/yr

(d) Drying Oven Emissions: The drying oven is powered by electricity and therefore no pollutant is emitted.

	SUMMAR			
Pollutant	Epoxy Dip Tank	Engine Test Stands	Space Heaters	Total Emissions
РМ	0.0	0.066	0.0	0.066
PM10	0.0	0.0005	0.1	0.1005
NOx	0.0	27.46	0.8	28.26
VOC	2.46	0.79	0.0	3.25
СО	0.0	5.7	0.6	6.3
S02	0.0	0.004	0.0	0.004

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, the department, or the appropriate local air pollution control agency."

Pollutant	Potential To Emit (tons/year)
PM	0.066
PM-10	0.1005
SO ₂	0.004
VOC	3.25
СО	6.3
NO _x	28.26

Justification for Approval level

(a) iPower Technologies, LLC is subject to 326 IAC 2-6.1 Minor Source Operating Permit (MSOP), since the potential to emit nitrogen oxides (NOx) are at levels greater than 25 tons per year but less than 100 tons per year. The MSOP will allow the source to construct and operate the new emission units.

Source Status

New Source PSD Definition (emissions after controls, based on 8,760 hours of operation per year at rated capacity):

	Limited Potential to Emit (tons/year)										
Process/facility	PM	NO _x	HAPs								
Epoxy Dip Tank	0.0	0.0	0.0	2.46	0.0	0.0	0.0				
Engine Test Stands	0.066	0.0005	0.004	0.79	5.7	27.46	0.0				
Natural Gas Space Heaters	0.0	0.1	0.0	0.0	0.6	0.8	0.0				
Total Emissions	0.066	0.1005	0.004	3.25	6.3	28.26	0.0				

(a) This new source is **not** a major stationary source because no attainment pollutant is emitted at a rate of 250 tons per year or greater and it is not in one of the 28 listed source categories. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.

County Attainment Status

The source is located in Madison County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO_2	attainment
Ozone	attainment
СО	attainment
Lead	not determined

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NOx) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Madison County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Madison County has been classified as attainment or unclassifiable for all the other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Part 70 Permit Determination

326 IAC 2-7 (Part 70 Permit Program)

This new source is not subject to the Part 70 Permit requirements because the potential to emit (PTE) of:

- (a) each criteria pollutant is less than 100 tons per year,
- (b) No single hazardous air pollutant (HAP) is emitted at the source, and
- (c) No combination of HAPs is emitted at the source.

This is the first air approval issued to this source.

Federal Rule Applicability

- (a) New Source Performance Standards (NSPS):
 - (a) 40 CFR Part 60.460, Subpart TT- Standards of Performance for Metal Coil Surface Coating. This rule applies to the following affected facilities in a metal coil surface coating operation: each prime coat operation, each finish coat operation, and each prime and finish operation combined when the finish coat is applied wet on wet over the prime coat and both coatings are cured simultaneously.
 - This NSPS is not applicable to the source because the stator coil metal that is being coated is already in the finished product stage. The metal is not in a flat metal strip or sheet that comes in rolls or coils.
 - (2) There are no other New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) National Emission Standards for Hazardous Air Pollutants (NESHAP) There are no NESHAP, 326 IAC 14, (40 CFR 63) applicable to this source

State Rule Applicability - Entire Source

- (a) 326 IAC 2-6 (Emission Reporting) This source is not subject to 326 IAC 2-6 (Emission Reporting), because it does not have the potential to emit more than one hundred (100) tons per year of any VOC, NOx, PM10, SO2, or CO.
- (b) 326 IAC 5-1 (Visible Emissions Limitations) Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:
 - (1) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
 - (2) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

(a) 326 IAC 8-2-4 (Coil Coating Operations) This rule establishes emission limitation for coating of any flat metal sheets or strips that comes in rolls or coils. This rule does not apply to the stator metal coil coating at this

- source, since they are already at the finished product stage when coated, and not when in flat metal strip or sheet stage.
- (b) 326 IAC 8-2-9 (Miscellaneous Metal Coating)
 The one (1) Epoxy Dip Tank, identified as PDG-U500 is not subject to this rule, because its actual VOC emissions are less than 15 pounds per day.
- (c) 326 IAC 6-3-2 (Process Operations)

 The stator coil coating is not subject to this rule, because dip tank coating has a 100% transfer efficiency which means that no PM overspray is emitted.
- (d) 326 IAC 6-2 (Indirect Heating Facilities) The ten (10) natural gas-fired space heaters are not subject to 326 IAC 6-2, because they are not sources of indirect heating.
- (e) 326 IAC 7-1 (Sulfur Dioxide Emission Limitations)
 The three (3) test stands are not subject to 326 IAC 7-1, because they do not emit SO2 at a rate of 25 tons per year or 10 pounds per hour.

Conclusion

The construction and operation of this stator engine components manufacturing plant shall be subject to the conditions of the attached **New Source Construction and Minor Source Operating Permit 095-14781-00106**.

Appendix A: Emissions Calculations Natural Gas Combustion Only MM BTU/HR <100 Small Industrial Boiler

Company Name: iPower Technologies, LLC

Address City IN Zip: 1819 W. 38th St., Anderson, Indiana 46013

10 nat. gas-fired space heaters w/ total MSOP No.: 095-14781 heat input rate of 1.75 PIt ID: 095-00106

Reviewer: Aida De Guzman

Date Application Received: August 13, 2001

Heat Input Capacity Potential Throughput

MMBtu/hr MMCF/yr

1.8

Pollutant

	PM*	PM10*	SO2	NOx	VOC	CO
Emission Factor in lb/MMCF	1.9	7.6	0.6	100.0	5.5	84.0
				**see below		
Potential Emission in tons/yr	0.0	0.1	0.0	0.8	0.0	0.6

^{*}PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

Note: Check the applicable rules and test methods for PM and PM10 when using the above emission factors to confirm that the correct factor is used (i.e., condensable included/not included).

^{**}Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Page 2 of 2 TSD App A

Appendix A: Emissions Calculations
VOC and Particulate
From Surface Coating Operations

Company Name: iPower Technologies, LLC

Address City IN Zip: 1819 Enterprise Dr., Anderson, Indiana 46013

MSOP No.: 095-14781 Plt ID: 095-00106

Reviewer: Aida De Guzman

Date Application Received: August 13, 2001

Material	Density (Lb/Gal)	Weight % Volatile (H20 & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water		Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Dip Tank PD6-U500																
Epoxy Mixture	9.9	15.40%	0.0%	15.4%	0.0%	84.60%	0.00123	300.000	1.52	1.52	0.56	13.49	2.46	0.00	1.80	100%

State Potential Emissions Add worst case coating to all solvents 0.56 13.49 2.46 0.00

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used